

Aluminium Bi-Fold Quotation/Order Form

Quote	Order	Date	1		1	Nui	mber			
Job Reference/Number					Collection Delivery					
Company Name					Date Required					
Address					Delivery Address					
Postcode					Delivery Postcode					
Telephone					Email					
Signed					Print					
Overall Width (mm	1)		Overall Heig	ght (r	(mm) Open In Open Out					
Including any cills or	frame extender	s all viewed f	from the outsid	le.						
P-06-100 Rebated Threshold P-06-130 Non Weather Rated Low Threshold					P-06-131 AW660 Non Thermally 70 Square Broken Low Bead Threshold Standard					
Configuration options										
		As viewe	ed from outsid	le						
	ons : total number	As viewe	ed from outsid	le						
Configuration	: total number	As viewe	ed from outsid	le						
Configuration of sashes If Master Doc please indicate	total number or is required the left (L)	As viewe	ed from outsid	le						
Configuration of sashes If Master Doc please indicat or right (R) Number of sa sliding to the	er is required the left (L) ushes folding/ LEFT	As viewe	ed from outsid	le						
Configuration of sashes If Master Doo please indicat or right (R) Number of sashiding to the Number of sashiding to the Please note: Even pwill have no external shootbolt locking on	er is required to left (L) shes folding/ LEFT shes folding/ RIGHT paned styles I access, Ily. Slave doors	As viewe	ed from outsid	le						
Configuration of sashes If Master Doo please indicat or right (R) Number of sa sliding to the Number of sa sliding to the Please note: Even pwill have no externa shootbolt locking on to have finger bolts	er is required to left (L) shes folding/ LEFT shes folding/ RIGHT paned styles I access, lly. Slave doors as standard.	As viewe		le	150mm	1	77mm	1900	nm	No cill
Configuration of sashes If Master Doo please indicat or right (R) Number of sa sliding to the Number of sa sliding to the Please note: Even p will have no externa shootbolt locking on to have finger bolts Drainage	er is required the left (L) shes folding/ LEFT shes folding/ RIGHT to aned styles I access, aly, Slave doors as standard. Concealed		95mm] 150mm	1	77mm		L	No cill
Configuration of sashes If Master Dod please indicat or right (R) Number of sashiding to the Number of sashiding to the Please note: Even puill have no externashootbolt locking on to have finger bolts	er is required to left (L) shes folding/ LEFT shes folding/ RIGHT paned styles I access, lly. Slave doors as standard.	Cill	95mm] 150mm	1	77mm		L	No cill g as standard
Configuration of sashes If Master Doo please indicat or right (R) Number of sa sliding to the Number of sa sliding to the Please note: Even p will have no externa shootbolt locking on to have finger bolts Drainage	cr is required the left (L) shes folding/ LEFT ushes folding/ RIGHT to aned styles I access, Ily. Slave doors as standard. Concealed None	Cill	95mm : (mm)	kle Ve		1			L	



Standard Single Colour Options		Standard Dual Colour Options (when Colour Plus is released)				
RAL 9005 Black Matt RAL 70	016 Anthracite Grey Matt	(When Colour Plus is released) RAL 9005 Black Matt RAL 9910 White High Gloss RAL 7016 Anthracite Grey Matt RAL 9910 White High Gloss				
RAL 8017 Brown Matt RAL 98	910 White High Gloss					
*RAL Inside	Colour	High Gloss Matt				
*RAL Outside	Colour	High Gloss Matt				
Marine guarantee required (please tick). *F	For marine environment application	ons please refer to disclaimer.				
The above will incur an additional colour set-up c	ost and extended lead times.					
Traffic Door Handle N	lon Locking T Handle	Locking T Handle				
Black White	Black White	Black White				
Satin Silver Chrome	Satin Silver Chrom	e Satin Silver Chrome				
Hinges and associated hardware to be black finis	sh as standard.	only on configurations without a traffic door.				
Glazed Yes No Standard 28mm g	lazing is 4mm Tough K Softcoat +	Argon + 4mmTough Low Iron Swiss Black Spacer Bar.				
height of up to 3000mm subject to wind load de We cannot guarantee any product installed withi	flection. n 50 metres of the coast, 50m o For any product fitted within 500	eight and no smaller than 500mm with a maximum i a source of pollution or 2 metres from a swimming metres of a hostile environment a recommended All frames are non-load bearing.				
Extra comments	by a Window manufacture to proceed v	I accept full responsibility even if the order has been completed by a Window Warehouse representative. Sizes shown are manufacture sizes and I therefore authorise Window Warehouse to proceed with manufacture. I have read and accepted the terms and conditions as stated on the Window Warehouse website.				
	Sign Name					
	Print Name					
	Date					

Window Warehouse Ltd

Head Office: Unit 1, Dragon Industrial Estate, Fitzherbert Road, Farlington, Portsmouth, Hamsphire PO6 1SQ Tel: 023 9232 7744 Fax: 023 9232 6611 E-mail: sales@window-warehouse.co.uk www.window-warehouse.co.uk