

RENOLIT EXOFOL Films. Cleaning made simple.



When something accidentally spills during installation.

Wherever there is construction, there is dirt, and a splash of plaster or paint can easily land on that brand new window frame. But be careful because abrasive or corrosive products such as scouring agents, white spirit or sharp-edged tools can cause permanent damage.

Hot tap water and ordinary washing-up liquid are sufficient to remove tile adhesive, paint or plaster residues. In these cases, use plenty of water and be patient. Soak the dirt thoroughly then rinse away the loosened particles, otherwise it acts like sandpaper. And for particularly stubborn cases such as rubber abrasion, there is RENOLIT EXOFOL Professional Cleaner.





For the annual spring clean.

With RENOLIT EXOFOL films, having clean window frames is a foregone conclusion, because dirt particles have difficulty sticking to their surface.

Regular household cleaning is easy. Hot tap water, a soft brush or sponge and a squirt of washing-up liquid are all that is needed to remove summer dust or winter dirt. Under no circumstances should you scrub or rub, otherwise the top layer of the film will be damaged and its protective effect impaired.





RENOLIT SE

Market Unit Exterior Solutions Horchheimer Str. 50 67547 Worms | Germany Phone: +49.6241.303.1040

RENOLIT Cramlington Limited

Station Road Northumberland, NE23 8AQ Cramlington | United Kingdom Phone: +44.1670.718222

exteriorsolutions@renolit.com www.renolit.com/exteriorsolutions



